# **Product Data Sheet**

# EasiFix Cove



#### Introduction

#### **Overview**

EasiFix Cove 100 and 127 is a 'C' profile gypsum plaster cove.

#### **Application**

Use it to conceal cable runs and mask settlement cracks.

| Product                        | Length | Corners             |
|--------------------------------|--------|---------------------|
| EasiFix 100                    | 2m     |                     |
| EasiFix 127                    | 2m     |                     |
| EasiFix Pre-mitred corners 100 |        | Internal            |
| EasiFix Pre-mitred corners 100 |        | Internal & External |
| EasiFix Pre-mitred corners 127 |        | Internal            |
| EasiFix Pre-mitred corners 127 |        | Internal & External |

#### Installation

#### **Preparation**

Ensure wall and ceiling backgrounds are sound, clean and dry, removing any wallpaper before attempting to fix the cove. For easier installation, draw guidelines along the wall and ceiling with a pencil at the appropriate distances. For Gyproc Cove 100, lines should be drawn at 67mm down the wall and 67mm across the ceiling. Scratch plastered or painted areas which will be in contact with the cove to provide a key for the adhesive and brush away any dust or loose material.

#### Cutting

Cut the product to the required length using a cove mitre block and a fine tooth saw.

## **Fixing**

Apply the adhesive in a 3mm thickness to both surfaces of the cove that will be in contact with the wall. For very dry plaster backgrounds or those with high suction, dampen down with a clean sponge and clean water immediately prior to adhesive application. This will prevent the adhesive from drying out too rapidly.

When installing the cove lightly nail the line marked on the wall to provide temporary support to the profile until the adhesive has set. Use two nails for each piece. These should be removed once the adhesive is set. Offer up the profile and push it firmly into position between the guidelines.

### **Conditions**

#### Standards

EN 14209:2017.

# Storage

Store in a dry place and keep out of sunlight.

# Recyclability

This product can be recycled.

#### Disposal

Segregate the product from non-gypsum waste for recycling where possible and dispose of it according to local authority requirements.

Okarno Ltd, Pasture Lane, Ruddington, Nottingham, NG11 6AE, Tel +44 (0) 115 984 5679, www.Okarnoltd.com Okarno Ltd registered in England, Company Number 4140239.Registered Office, Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU. The Okarno logo is a registered trademark of BPB United Kingdom Limited part of the Saint-Gobain Group

Okarno reserves the right to revise product specifications without notice. The information in this document is correct to the best of our knowledge at the time of publication. It is the user's responsibility to ensure that it remains current prior to use. The information in this document is for guidance only and should not be read in isolation. Users should read and familiarise themselves with all the information contained in this document and ensure that they are fully conversant with the products and systems being used before installation.

<u>Telephone:</u> 0800 032 6345 <u>Email: OkarnoTechnical@Saint-Gobain.com</u>

©Okanro September 2023 PDS - EFC - 2